

**DIMENSIONS AND WEIGHTS OF STEEL PIPE TO
ANSI B 36. 10-79**

Metric Size (mm)	Outside Diameter		Wall Thickness		Weight		Identification				
	Inches	mm	Inches	mm	Inches	mm	API Specifications			W.T. Std - XS XSS	Nº Schedule
1/8	0.405	10.3	0.068	1.73	0.24	0.37	X			STD	40
	0.405	10.3	0.095	2.41	0.31	0.47	X			XS	80
1/4	0.540	13.7	0.088	2.24	0.42	0.63	X			STD	40
	0.540	13.7	0.119	3.02	0.54	0.80	X			XS	80
3/8	0.675	17.1	0.091	2.31	0.57	0.84	X			STD	40
	0.675	17.1	0.126	3.20	0.74	1.10	X			XS	80
1/2	0.840	21.3	0.109	2.77	0.85	1.27	X			STD	40
	0.840	21.3	0.147	3.73	1.09	1.62	X			XS	80
	0.840	21.3	0.188	4.78	1.31	1.95					160
	0.840	21.3	0.294	7.47	1.71	2.55	X			XXS	
3/4	1.050	26.7	0.113	2.87	1.13	1.69	X			STD	40
	1.050	26.7	0.154	3.91	1.47	2.20	X			XS	80
	1.050	26.7	0.219	5.56	1.94	2.90					160
	1.050	26.7	0.308	7.82	2.44	3.64	X			XXS	
1	1.315	33.4	0.133	3.38	1.68	2.50	X			STD	40
	1.315	33.4	0.179	4.55	2.17	3.24	X			XS	80
	1.315	33.4	0.250	6.35	2.84	4.24					160
	1.315	33.4	0.358	9.09	3.66	5.45	X			XXS	
1 1/4	1.660	42.2	0.140	3.56	2.27	3.39	X			STD	40
	1.660	42.2	0.191	4.85	3.00	4.47	X			XS	80
	1.660	42.2	0.250	6.35	3.76	5.61					160
	1.660	42.2	0.382	9.70	5.21	7.77	X			XXS	
1 1/2	1.900	48.3	0.145	3.68	2.72	4.05	X			STD	40
	1.900	48.3	0.200	5.08	3.63	5.41	X			XS	80
	1.900	48.3	0.281	7.14	4.86	7.25					160
	1.900	48.3	0.400	10.15	6.41	9.56	X			XXS	



ERW & SEAMLESS PIPES



DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Metric Size (mm)	Outside Diameter		Wall Thickness		Weight		Identification				
	Inches	mm	Inches	mm	Inches	mm	API Specifications			W.T. Std - XS XSS	Nº Schedule
2	2.375	60.3	0.083	2.11	2.03	3.03	X	X			
	2.375	60.3	0.109	2.77	2.64	3.93	X	X			
	2.375	60.3	0.125	3.18	3.00	4.48	X	X			
	2.375	60.3	0.141	3.58	3.36	5.01	X	X			
	2.375	60.3	0.154	3.91	3.65	5.44	X	X			
	2.375	60.3	0.172	4.37	4.05	6.03	X	X		STD	40
	2.375	60.3	0.188	4.78	4.39	6.54	X	X			
	2.375	60.3	0.218	5.54	5.02	7.48	X	X		XS	80
	2.375	60.3	0.250	6.35	6.67	8.45	X	X			
	2.375	60.3	0.281	7.14	6.28	9.36	X	X			
	2.375	60.3	0.344	8.74	7.46	11.11					160
	2.375	60.3	0.436	11.07	9.03	13.44	X	X		XXS	
2 1/2	2.875	73.0	0.083	2.11	2.47	3.69	X	X			
	2.875	73.0	0.109	2.77	3.22	4.80	X	X			
	2.875	73.0	0.125	3.18	3.67	5.48	X	X			
	2.875	73.0	0.141	3.58	4.12	6.13	X	X			
	2.875	73.0	0.156	3.96	4.53	6.74	X	X			
	2.875	73.0	0.172	4.37	4.97	7.40	X	X			
	2.875	73.0	0.188	4.78	5.40	8.04	X	X			
	2.875	73.0	0.203	5.16	5.79	8.63	X	X		STD	40
	2.875	73.0	0.216	5.49	6.13	9.14	X	X			
	2.875	73.0	0.250	6.35	7.01	10.44	X	X			
	2.875	73.0	0.276	7.01	7.66	11.41	X	X		XS	80
	2.875	73.0	0.375	9.53	10.01	14.92					160
	2.875	73.0	0.552	14.02	13.69	20.39	X	X		XXS	
3	3.500	88.9	0.083	2.11	3.03	4.52	X	X			
	3.500	88.9	0.109	2.77	3.95	5.88	X	X			
	3.500	88.9	0.125	3.18	4.51	6.72	X	X			
	3.500	88.9	0.141	3.58	5.06	7.53	X	X			
	3.500	88.9	0.156	3.96	5.57	8.29	X	X			

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Metric Size (mm)	Outside Diameter		Wall Thickness		Weight		Identification				
	Inches	mm	Inches	mm	Inches	mm	API Specifications			W.T. Std - XS XSS	Nº Schedule
3	3.500	88.9	0.172	4.37	6.11	9.11	X	X			
	3.500	88.9	0.188	4.78	6.65	9.92	X	X			
	3.500	88.9	0.216	5.49	7.58	11.29	X	X		STD	40
	3.500	88.9	0.250	6.35	8.68	12.93	X	X			
	3.500	88.9	0.281	7.14	9.66	14.40	X	X		XS	80
	3.500	88.9	0.300	7.62	10.25	15.27	X	X			160
	3.500	88.9	0.438	11.13	14.32	21.35					
	3.500	88.9	0.600	15.24	18.58	27.68	X	X		XXS	
3 1/2	4.000	101.6	0.083	2.11	3.47	5.18	X	X			
	4.000	101.6	0.109	2.77	4.53	6.75	X	X			
	4.000	101.6	0.125	3.18	5.17	7.72	X	X			
	4.000	101.6	0.141	3.58	5.81	8.65	X	X			
	4.000	101.6	0.156	3.96	6.40	9.53	X	X			
	4.000	101.6	0.172	4.37	7.03	10.48	X	X			
	4.000	101.6	0.188	4.78	7.65	11.41	X	X			
	4.000	101.6	0.226	5.74	9.11	13.57	X	X		STD	40
	4.000	101.6	0.250	6.35	10.01	14.92	X	X			
	4.000	101.6	0.281	7.14	11.16	16.63	X	X			
	4.000	101.6	0.318	8.08	12.50	18.63	X	X		XS	80
4	4.500	114.3	0.083	2.11	3.92	5.84	X	X	X		
	4.500	114.3	0.109	2.77	5.11	7.62	X	X	X		
	4.500	114.3	0.125	3.18	5.84	8.71	X	X	X		
	4.500	114.3	0.141	3.58	6.56	9.77	X	X	X		
	4.500	114.3	0.156	3.96	7.24	10.78	X	X	X		
	4.500	114.3	0.172	4.37	7.95	11.85	X	X	X		
	4.500	114.3	0.188	4.78	8.66	12.91	X	X	X		
	4.500	114.3	0.203	5.16	9.32	13.89	X	X	X		
	4.500	114.3	0.219	5.56	10.01	14.91	X	X	X		
	4.500	114.3	0.237	6.02	10.79	16.07	X	X	X		
	4.500	114.3	0.250	6.35	11.35	16.90	X	X	X		
	4.500	114.3	0.281	7.14	12.66	18.87	X	X	X		
	4.500	114.3	0.312	7.92	13.96	20.78	X	X	X		
	4.500	114.3	0.337	8.56	14.98	22.32	X	X	X		
	4.500	114.3	0.438	11.13	19.00	28.32	X	X	X	XS	80
	4.500	114.3	0.531	13.49	22.51	33.54	X	X	X		120
	4.500	114.3	0.674	17.12	27.54	41.03	X	X	X	XXS	160
5	5.563	141.3	0.083	2.11	4.86	7.24	X		X		
	5.563	141.3	0.125	3.18	7.26	10.83	X		X		

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Metric Size (mm)	Outside Diameter		Wall Thickness		Weight		Identification				
	Inches	mm	Inches	mm	Inches	mm	API Specifications			W.T. Std - XS XSS	Nº Schedule
							5L 3/82	5LX 3/82	5LS 3/82		
5	5.563	141.3	0.156	3.96	3.96	9.01	X	X		STD	40
	5.563	141.3	0.188	4.78	4.78	10.79	X	X			
	5.563	141.3	0.219	5.56	5.56	12.50	X	X			
	5.563	141.3	0.258	6.55	6.55	14.62	X	X			
	5.563	141.3	0.281	7.14	7.14	15.85	X	X			
	5.563	141.3	0.312	7.92	7.92	17.50	X	X		XS	80
	5.563	141.3	0.344	8.74	8.74	19.17	X	X			
	5.563	141.3	0.375	9.53	9.53	20.78	X				
	5.563	141.3	0.500	12.70	12.70	27.04	X	X		XSS	160
	5.563	141.3	0.625	15.88	15.88	32.96	X	X			
6	6.625	168.3	0.083	2.11	2.11	5.80	X	X	X	STD	40
	6.625	168.3	0.109	2.77	2.77	7.59	X	X	X		
	6.625	168.3	0.125	3.18	3.18	8.68	X	X	X		
	6.625	168.3	0.141	3.58	3.58	9.76	X	X	X		
	6.625	168.3	0.156	3.96	3.96	10.78	X	X	X		
	6.625	168.3	0.172	4.37	4.37	11.88	X	X	X		
	6.625	168.3	0.188	4.78	4.78	12.92	X	X	X		
	6.625	168.3	0.203	5.16	5.16	13.92	X	X	X		
	6.625	168.3	0.219	5.56	5.56	14.98	X	X	X		
	6.625	168.3	0.250	6.35	6.35	17.02	X	X	X	XS	80
	6.625	168.3	0.280	7.11	7.11	18.97	X	X	X		
	6.625	168.3	0.312	7.92	7.92	21.04	X	X	X		
	6.625	168.3	0.344	8.74	8.74	23.08	X	X	X		
	6.625	168.3	0.375	9.53	9.53	25.03	X	X	X		
	6.625	168.3	0.432	10.97	10.97	28.57	X	X	X		
	6.625	168.3	0.500	12.70	12.70	32.71	X	X	X		
	6.625	168.3	0.562	14.27	14.27	36.39	X	X	X		120
	6.625	168.3	0.625	15.88	15.88	40.05	X	X	X		
	6.625	168.3	0.719	18.26	18.26	45.35	X	X	X	XSS	160
	6.625	168.3	0.864	21.95	21.95	53.16	X	X	X		
8	8.625	219.1	0.125	3.18	3.18	11.35	X	X	X		
	8.625	219.1	0.156	3.96	3.96	14.11	X	X	X		
	8.625	219.1	0.188	4.78	4.78	16.94	X	X	X		
	8.625	219.1	0.203	5.16	5.16	18.26	X	X	X		
	8.625	219.1	0.250	6.35	6.35	22.00	X	X	X		

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Metric Size (mm)	Outside Diameter		Wall Thickness		Weight		Identification				
	Inches	mm	Inches	mm	Inches	mm	API Specifications			W.T. Std - XS XSS	Nº Schedule
							5L 3/82	5LX 3/82	5LS 3/82		
8	8.625	219.1	0.219	5.56	19.66	29.28	X	X	X	STD	20 30 40
	8.625	219.1	0.250	6.35	22.36	33.31	X	X	X		
	8.625	219.1	0.277	7.04	24.70	36.81	X	X	X		
	8.625	219.1	0.312	7.92	27.70	41.24	X	X	X		
	8.625	219.1	0.322	8.18	28.55	42.55	X	X	X		
	8.625	219.1	0.344	8.74	30.42	45.34	X	X	X		
	8.625	219.1	0.375	9.53	33.04	49.25	X	X	X	60	
	8.625	219.1	0.406	10.31	35.64	53.08					
	8.625	219.1	0.438	11.13	38.30	57.08	X	X	X		
	8.625	219.1	0.500	12.70	43.39	64.64	X	X	X	XS	80
	8.625	219.1	0.562	14.27	48.40	72.08	X	X	X		
	8.625	219.1	0.594	15.09	50.95	75.92				100	
	8.625	219.1	0.625	15.88	53.40	79.58	X	X	X		
	8.625	219.1	0.719	18.26	60.71	90.44	X	X	X		
	8.625	219.1	0.812	20.62	67.76	100.92					
	8.625	219.1	0.875	22.23	72.42	107.92	X			XSS	120 140 160
	8.625	219.1	0.906	23.01	74.69	111.27					
10	10.750	273.1	0.156	3.96	17.65	26.28	X	X	X	STD	20 30 40 60 80 100 120 140 160
	10.750	273.1	0.188	4.78	21.21	31.63	X	X	X		
	10.750	273.1	0.203	5.16	22.87	34.09	X	X	X		
	10.750	273.1	0.219	5.56	24.63	36.68	X	X	X		
	10.750	273.1	0.250	6.35	28.04	41.77	X	X	X		
	10.750	273.1	0.279	7.09	31.20	46.51	X	X	X		
	10.750	273.1	0.307	7.80	34.24	51.03	X	X	X		
	10.750	273.1	0.344	8.74	38.23	56.98	X	X	X		
	10.750	273.1	0.365	9.27	40.48	60.31	X	X	X		
	10.750	273.1	0.438	11.13	48.24	71.90	X	X	X		
	10.750	273.1	0.500	12.70	54.74	81.55	X	X	X	XS	60
	10.750	273.1	0.562	14.27	61.15	91.08	X	X	X		
	10.750	273.1	0.594	15.09	64.43	96.01				80	
	10.750	273.1	0.625	15.88	67.58	100.73	X	X	X		
	10.750	273.1	0.719	18.26	77.03	114.75	X	X	X		
	10.750	273.1	0.812	20.62	86.18	128.38	X				
	10.750	273.1	0.844	21.44	89.29	133.06				XSS	120 140 160
	10.750	273.1	1.000	25.40	104.13	155.15					
	10.750	273.1	1.125	28.58	115.64	172.33					

DIMENSIONS AND WEIGHTS OF STEEL PIPE TO ANSI B 36. 10-79

Metric Size (mm)	Outside Diameter		Wall Thickness		Weight		Identification				
							API Specifications			W.T. Std - XS XSS	Nº Schedule
	Inches	mm	Inches	mm	Inches	mm	5L 3/82	5LX 3/82	5LS 3/82		
12	12.750	323.9	0.172	4.37	23.11	34.43	X	X	X	STD	20
	12.750	323.9	0.188	4.78	25.22	37.62	X	X	X		
	12.750	323.9	0.203	5.16	27.20	40.56		X	X		
	12.750	323.9	0.219	5.56	29.31	43.65	X	X	X		
	12.750	323.9	0.250	6.35	33.38	49.73	X	X	X		
	12.750	323.9	0.281	7.14	37.42	55.77	X	X	X		
	12.750	323.9	0.312	7.92	41.45	61.71	X	X	X		
	12.750	323.9	0.330	8.38	43.77	65.20	X	X	X		
	12.750	323.9	0.344	8.74	45.58	67.93	X	X	X		
	12.750	323.9	0.375	9.53	49.56	73.88	X	X	X		
	12.750	323.9	0.406	10.31	53.52	79.73		X	X		
	12.750	323.9	0.438	11.13	57.59	85.84	X	X	X		
	12.750	323.9	0.500	12.70	65.42	97.46	X	X	X		
	12.750	323.9	0.562	14.27	73.15	108.96	X	X	X		
	12.750	323.9	0.625	15.88	80.93	120.62	X	X	X		
	12.750	323.9	0.688	17.48	88.63	132.08	X	X	X		
	12.750	323.9	0.750	19.05	96.12	143.21	X	X	X		
	12.750	323.9	0.812	20.62	103.53	154.21	X	X	X		
	12.750	323.9	0.844	21.44	107.32	159.91					
	12.750	323.9	0.875	22.23	110.97	165.37	X	X	X		
12.750	323.9	1.000	25.40	125.49	186.97						
12.750	323.9	1.125	28.58	139.67	208.14						
12.750	323.9	1.312	33.32	160.27	238.76						
14	14.000	355.6	0.188	4.78	27.73	41.35	X	X	X	STD	10
	14.000	355.6	0.203	5.16	29.91	44.59	X		X		
	14.000	355.6	0.210	5.33	30.93	46.04		X	X		
	14.000	355.6	0.219	5.56	32.23	47.99		X	X		
	14.000	355.6	0.250	6.35	36.71	54.69	X	X	X		
	14.000	355.6	0.281	7.14	41.17	61.35	X	X	X		
	14.000	355.6	0.312	7.92	45.61	67.90	X	X	X		
	14.000	355.6	0.344	8.74	50.17	74.76	X	X	X		
	14.000	355.6	0.375	9.53	54.57	81.33	X	X	X		
	14.000	355.6	0.406	10.31	58.94	87.79		X	X		
	14.000	355.6	0.438	11.13	63.44	94.55	X	X	X		
	14.000	355.6	0.469	11.91	67.78	100.94	X	X	X		
	14.000	355.6	0.500	12.70	72.09	107.39	X	X	X		
	14.000	355.6	0.562	14.27	80.66	120.11	X	X	X		
	14.000	355.6	0.594	15.09	85.05	126.71					
	14.000	355.6	0.625	15.88	89.28	133.03	X	X	X		

